

**ROLLING SLIDE PARTS**

**Publication number:** JP10047334

**Publication date:** 1998-02-17

**Inventor:** KADOKAWA SATOSHI; MURAKAMI YASUO

**Applicant:** NIPPON SEIKO KK

**Classification:**

**- International:** *F16H53/06; C21D9/40; F16C3/02; F16H53/00; C21D9/40; F16C3/02; (IPC1-7): F16C3/02; C21D9/40; F16H53/06*

**- European:**

**Application number:** JP19960204588 19960802

**Priority number(s):** JP19960204588 19960802

**Report a data error here**

**Abstract of JP10047334**

**PROBLEM TO BE SOLVED:** To ensure durability and wear resistance by regulating the quantity of carbide in a surface layer, hardness, the decomposition ratio of residual austenite associated with surface reinforcing work and surface roughness respectively to the specific value. **SOLUTION:** This rolling slide part is used in the state of coming in rolling contact or sliding contact with another opposed part. In the case where a range of 0-50 $\mu$  m in depth from the surface is made a surface layer part, the rate of carbide contained in this surface layer is 10-25vol%, the decomposition ratio of residual austenite of the surface layer part to the initial value is 1/10-3/10, the hardness of the surface layer part is Hv830-Hv960, and surface roughness is 25 $\mu$  m. Sufficient durability and wear resistance can thereby be ensured even under such a severe condition as to be lubricated only by lubricating oil with soot and other insoluble components mixed therein.

---

Data supplied from the **esp@cenet** database - Worldwide